

Online Transformerless UPS



Main Features:

- Online double conversion
- High input power factor
- Wide input voltage range
- Automatic bypass
- Monitoring via SNMP
- Intelligent RS232+USB+EPO communication port
- Internal battery bank
- 24 months warranty

Specifications:

MODEL	ELT 6000	ELT 1110S
	INPUT	
Voltage (Vac)	120~275 (L,N, G)	
Frequency (Hz)	50/60±5% (50/60 Hz ±10% settings)	
Power Factor	>0.99	
	OUTPUT	
Capacity(VA)	6000	10000
Power Factor	0.8(0.9 is optional)	
Voltage (V)	220V/230V/240V±2%	
Frequency (Hz)	50/60±0.2% (battery mode)	
Waveform	Pure Sine wave, THD<3% (Linear Load)	
Transfer Time (ms)	0	
Overload capacity	105~129% load for 10 mins, 130~150% load for 1 min, above 150% load for 1 sec	
	BATTERY	
Voltage (Vdc)	192	
Battery Type	16x7Ah 12V/External	
Charger Current(A)Max	1/6	
	OTHER	
Protection	Low battery, overload, over temperature and short circuit	
Display	LCD displays parameters of UPS	
Alarm	Abnormal AC input, low battery, UPS failure	
Communication Interface	RS232+USB+EPO (Dry contact SNMP are optional)	
Relative humidity	0~95% (no condensation)	
Working Temperature	0~40°C	
Noise (dB)	<55	
Dimension(mm) (WxDxH)	255x565x700/ 255x565x500	
Weight (kg)	69/23	70/24